

DOLPHIN TECHNOLOGY PRODUCT OFFERING

I/O

Dolphin Technology offers an extensive array of Interface IP, all of which has been optimized for ultra high performance across all processes supported. Our I/O portfolio includes: Standard I/O (General Purpose I/O or GPIO), Specialty I/O (bus-specific I/O), NAND Flash I/O and DDRx & LPDDRx I/O.

We specialize in Staggered, Inline and Flip Chip pads with aggressive pitch for the most demanding designs, whether pad or core limited. Plus, our I/O Compiler enables us to customize the entire library based on process-specific and chip-specific options.

	5nm	7nm	12/16 nm	22/28 nm	40nm	55nm	65nm	80nm	90nm
GENERAL PURPOSE I/O									
I/O drive strengths 2/4/6/8/10/12 mA	●	●	●	●	●	●	●	●	●
1.5V Xtrs, 1.8V output drive/2.5V Tolerant	●								
1.5V Xtrs, 1.8V/2.5V output drive Capable	●								
1.8V Xtrs, 1.8V output drive/3.3V Tolerant		●	●						
1.8V Xtrs, 1.8V/3.3V output drive Capable		●	●						
1.8V Xtrs, 1.8V output drive/2.5V/3.3V Tolerant				●	●	●	●	●	●
1.8V Xtrs, 1.8V/2.5V/3.3V output drive Capable				●	●	●	●	●	●
2.5V Xtrs, 2.5V output drive/3.3V Tolerant				●	●	●	●	●	●
2.5V Xtrs, 2.5V/3.3V output drive Capable				●	●	●	●	●	●

DDR I/O

Configurable single-ended and differential I/O's	●	●	●	●	●	●	●	●	●
DDR4/3/2 & LPDDR4/3/2 I/O with PVT Compensation and PVT compensated internal termination RTT using 1.8V Xtrs	●	●	●	●					
DDR4/3/2 & LPDDR4/3/2 I/O with PVT Compensation and PVT compensated internal termination RTT using 2.5V Xtrs	●	●	●	●					
DDR3/2/1 & LPDDR2/1 I/O with PVT Compensation and PVT compensated internal termination RTT using 1.8V Xtrs					●	●	●	●	●
DDR3/2/1 & LPDDR2/1 I/O with PVT Compensation and PVT compensated internal termination RTT using 2.5V Xtrs					●	●	●	●	●

NAND FLASH I/O

ONFI 4.2/4/3/2/1 and Toggle 2/1 NAND compliant	●	●	●	●	●	●	●		
Configurable single-ended and differential I/O's	●	●	●	●	●	●	●		
NAND Flash I/O with PVT Compensation and PVT compensated internal termination RTT using 1.8V Xtrs	●	●	●	●	●	●	●		
Drive capability up to 80pF	●	●	●	●	●	●	●		

SPECIAL PURPOSE I/O

LVPECL I/O with PVT Compensation	●	●	●	●	●	●	●	●	●
LVDS/LVPECL Combo with PVT Compensation	●	●	●	●	●	●	●	●	●
PCI	●	●	●	●	●	●	●	●	●
I2C/I3C	●	●	●	●	●	●	●	●	●

I/O FEATURES

Libraries include configurable I/O's, power cells, fillers, spacers, and analog or calibration cells	●	●	●	●	●	●	●	●	●
Pad design with 25um pitch	●	●	●	●	●	●	●	●	●
Supports wirebond/CUP and flipchip packages	●	●	●	●	●	●	●	●	●
Programmable metal stack options	●	●	●	●	●	●	●	●	●
4 different slew rate options	●	●	●	●	●	●	●	●	●

Front End views are available under NDA. For more information, [click here](#) or contact sales@dolphin-ic.com



Built-in JTAG Logic for testability	●	●	●	●	●	●	●	●	●
Input/Output registers options	●	●	●	●	●	●	●	●	●
Bus-hold(sustain) and pull-up/pull-down options	●	●	●	●	●	●	●	●	●
Built-in ESD and Latchup Prevention circuits	●	●	●	●	●	●	●	●	●

Front End views are available under NDA. For more information, [click here](#) or contact sales@dolphin-ic.com